

SECTION 1 - IDENTIFICATION

Product Identifier

Product Number(s) E8250CT
 Product Name TREEKOTE™ Tree Wound Dressing

Other Means of Identification None

Recommended Use and Restrictions on Use

Recommended Use Tree wound dressing.
 Restrictions on Use None Identified

24 hr Emergency
 Phone Number

800-255-3924
 (Chem-Tel)

MANUFACTURER DETAILS		SUPPLIER DETAILS	
Name	Chem-Pak, Inc.	Name	Eaton Brothers Corp.
Address	242 Corning Way Martinsburg WV 25405	Address	PO Box 60 Hamburg NY 14075
Phone Number	800-336-9828	Phone Number	716-649-8250
Fax Number	304-262-9643	Fax Number	716-649-9466

SECTION 2 - IDENTIFICATION

Hazard Classification

HEALTH HAZARDS				PHYSICAL HAZARDS					
Acute Tox. Oral	4	Mutagenicity	<input type="checkbox"/>	Unstable Explosive	<input type="checkbox"/>	Refrigerated Liq. Gas	<input type="checkbox"/>	Pyrophoric Solid	<input type="checkbox"/>
Acute Tox. Skin	<input type="checkbox"/>	Carcinogenicity	<input type="checkbox"/>	Explosive	<input type="checkbox"/>	Flammable Liquid	<input type="checkbox"/>	Emits Flammable Gas	<input type="checkbox"/>
Acute Tox. Inhalation	<input type="checkbox"/>	Tox. to Reproduction	<input type="checkbox"/>	Flammable Gas	<input type="checkbox"/>	Flammable Solid	<input type="checkbox"/>	Oxidizing Liquid	<input type="checkbox"/>
Skin Irritation	<input type="checkbox"/>	STOT SE	<input type="checkbox"/>	Aerosol	1	Self-Reactive Sub.	<input type="checkbox"/>	Oxidizing Solid	<input type="checkbox"/>
Eye Irritation	<input type="checkbox"/>	STOT RE	<input type="checkbox"/>	Oxidizing Gas	<input type="checkbox"/>	Pyrophoric Liquid	<input type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>
Resp. Sensitization	<input type="checkbox"/>	Aspiration Hazard	<input type="checkbox"/>	Gas Under Pressure	X	Self-Heating Substance	<input type="checkbox"/>	Corrosive to Metal	<input type="checkbox"/>
Skin Sensitization	<input type="checkbox"/>		<input type="checkbox"/>	ENVIRONMENTAL HAZARDS (GHS Rev 3 Only)					
	<input type="checkbox"/>		<input type="checkbox"/>	Aquatic Acute	<input type="checkbox"/>	Aquatic Chronic	3	Ozone Depleting	<input type="checkbox"/>

Signal Word

Danger

Hazard Pictograms



Hazard Statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Toxic to aquatic life with long lasting effects.

Precautionary Statements

General Keep out of reach of children.
Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release into the environment.
Response IF SWALLOWED: Immediately call a POISON CENTER or doctor, if you feel unwell. Rinse mouth. Collect spillage.
Storage Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



SAFETY DATA SHEET

TREEKOTE™ Tree Wound Dressing

Part No. E8250CT Aerosol

November 16, 2015

Revision 1

Page 2 of 7

Disposal	Dispose of contents/container in accordance with local regulations.
Hazards Not Otherwise Classified	None identified.
Unknown Acute Toxicity	24 % by wt

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

ID	INGREDIENT	CAS NUMBER	% WT RANGE*
1	Trans-1,2-Dichloroethylene	0000156-60-5	30 - 60
2	Asphalt, Oxidized	0064742-93-4	15 - 40
3	Liquefied Petroleum Gas	0068476-86-8	10 - 30
4	Stoddard Solvent	0008052-41-3	5 - 10
5	1,2,4-Trimethyl Benzene	0000095-63-6	1 - 5
6	Cumene	0000098-82-8	0.1 - 1
7	Xylene	0001330-20-7	0.1 - 1
8	Ethyl Benzene	0000100-41-4	0.1 - 1

* Exact percentages of composition withheld as trade secret

SECTION 4 - FIRST AID MEASURES

Description of First-Aid Measures

General	If exposed or concerned seek medical advice/attention.
Eye Contact	Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.
Skin Contact	Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.
Ingestion	Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.
First-Aid Responder Protection	Wear adequate personal protective equipment based on the nature and severity of the emergency.

Most Important Symptoms and Effects, Both Acute and Delayed

Eye Contact	Liquid contact may cause pain along with moderate eye irritation.
Skin Contact	Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.
Ingestion	Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, or possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.
Inhalation	Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.

Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	Stoddard Solvent sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmia in individuals exposed. Use of sympathomimetic drugs should be avoided. If ingested, the material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left later lateral decubitus position.
Specific Treatments/Antidotes	No information available.
Immediate Medical Attention	No information available.

SECTION 5 - FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media	Water, CO2, dry chemical, or universal aqueous film forming foam
Unsuitable Extinguishing Media	Water jet



SAFETY DATA SHEET

TREEKOTE™ Tree Wound Dressing

Part No. E8250CT Aerosol

November 16, 2015

Revision 1

Page 3 of 7

Specific Hazards Arising from the Chemical or Mixture

Decomposition Products	Oxides of carbon (CO, CO ₂), smoke, and/or vapors
Hazards from the Product	CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. In a fire or if heated, a pressure increase will occur which may result in the container bursting. Vapours heavier than air may spread along the ground and travel to an ignition source.

Advice for Firefighters

Protective Actions	Use water spray to cool fire exposed containers as contents may rupture violently from heat developed pressure.
Protective Equipment	As with any fire wear SCBA pressure-demand, MSHA/NIOSH approved, and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel	No action should be taken by non-emergency personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Responders	Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel.

Environmental Precautions

Precautions	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
--------------------	---

Methods and Materials for Containment and Cleaning Up

Containment Procedures	Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents. DO NOT use combustible material such as sawdust.
Cleanup Procedures	Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
Other Information	Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.
Prohibited Materials	Combustible absorbent material such as sawdust, use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling

General Handling Precautions	KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Wash hands after use.
Hygiene Recommendations	Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

Conditions for Safe Storage Including Any Incompatibilities

Storage Requirements	Storage of individual cans should be done in an area below 50 °C (122 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 3 Aerosol.
Incompatibilities	Segregate storage away from materials indicated in Section 10



SAFETY DATA SHEET

TREEKOTE™ Tree Wound Dressing

Part No. E8250CT Aerosol

November 16, 2015

Revision 1

Page 4 of 7

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits

ID	PEL	OSHA		IDLH	NIOSH			TLV	ACGIH		AIHA WEEL
		STEL	CEILING		REL	STEL	CEILING		STEL	CEILING	
1	200 ppm	–	–	1000 ppm	–	–	–	200 ppm	–	–	–
2	–	–	–	100 ppm	–	–	5 mg/m ³	0.5 mg/m ³	–	–	–
3	1000 ppm	–	–	200 ppm	1000 ppm	–	1800 mg/m ³	1000 ppm	–	–	–
4	500 ppm	–	–	20000 mg/m ³	350 mg/m ³	–	–	100 ppm	–	–	–
5	–	–	–	–	25 ppm	–	–	25 ppm	–	–	–
6	50 ppm	–	–	900 ppm	50 ppm	–	–	50 ppm	–	–	–
7	100 ppm	–	–	900 ppm	100 ppm	150 ppm	–	100 ppm	150 ppm	–	–
8	100 ppm	–	–	800 ppm	100 ppm	125 ppm	–	20 ppm	–	–	–

Biological Exposure Indices

ID	DETERMINANT	SAMPLING TIME	BEI	NOTATION
7	Methylhippuric acids in urine	End of shift	1.6 g/g creatinine	–

Other Control Parameters Not Available

Appropriate Engineering Control

Engineering Measures

Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

Individual Protection Measures

Hygiene Considerations

Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.

Thermal Protection

This product does not present a thermal hazard.

Respiratory Protection

An approved respirator with organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

Skin Protection

For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

Eye/Face Protection

Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

Other Protective Equipment

Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Properties

Boiling Point	> 47.8 °C (118.0 °F)	Melting / Freezing Point	Not Determined
Flash Point, Liquid	> 2.2 °C (36.0 °F)	Flash Point, Propellant	-104.4 °C (-156.0 °F)
Explosive Limits	6.70% - 18.00%	Autoignition Temperature, Liquid	Not Determined
Flammability	Extremely Flammable Aerosol	Relative Density (H ₂ O = 1)	0.858 g/cc
Molecular Weight	Not Available	Weight	7.161 lbs/gal
Vapor Pressure	70.00 psig	pH	Not Available
Vapor Density	Not Available	Evaporation Rate	Not Available
Form	Pressurized Product	Partition Coefficient	Not Available
Viscosity	Not Available	Refractive Index	Not Available
Odor Threshold	Not Available	Heat of Combustion (ΔH _c)	Not Available
Odor	Petroleum Odor	Water Solubility	Not Available



SAFETY DATA SHEET

TREEKOTE™ Tree Wound Dressing

Part No. E8250CT Aerosol

November 16, 2015

Revision 1

Page 5 of 7

Appearance / Color Dark Liquid Decomposition Temperature Not Available

Air Quality Properties

Percent Volatile	77% Wt (78% Vol) Max	VOC Regulatory	5.463 lbs/gal (654.497 g/L)
Percent VOC	77% Wt (78% Vol) Max	VOC Actual	5.463 lbs/gal (654.497 g/L)
Percent HAP	1% Wt (1% Vol) Max	HAP Content	0.056 lbs/gal (6.608 g/L)
Solids/Non Volatile Content	24% Wt (23% Vol) Max	Maximum Incremental Reactivity	1.404 g O3/g
Global Warming Potential	1.600		

SECTION 10 - STABILITY AND REACTIVITY

Reactivity No specific test data related to reactivity is available for this product or its ingredients.

Chemical Stability This product is stable.

Hazardous Reactions Under normal conditions of storage and use, hazardous reactions are not expected to occur.

Conditions to Avoid Keep away from heat, sparks, flame, and red hot metal.

Material Incompatibility Chlorine Dioxide, Chlorosulfuric Acid, Dichlorohydrantion, Difluoromethylene Dihyopfluorite, Dinitrogen Tetroxide And Pentoxide, Nitric Acid, Sodium, Sodium Hydroxide, Strong Oxidizing Agents, Sulfuric Acid

Decomposition Productions Oxides of Carbon, Hydrogen Chloride fumes, Phosgene may be formed depending on fire conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity Estimates (mixture)

Oral LD₅₀ 1478 mg/kg

Dermal LD₅₀ 4496 mg/kg

Inhalation LC₅₀ 1522 mg/L 4-hour

Acute Toxicity on Ingredients

ID	ORAL LD50		DERMAL LD50		INHALATION LC50		
	VALUE	SPECIES	VALUE	SPECIES	VALUE	TIME	SPECIES
1	-	-	-	-	164000 ppm	4h	rat
2	89840 mg/kg	rat	-	-	-	-	-
3	>5000 mg/kg	rat	>2000 mg/kg	rabbit	-	-	-

Health Hazard Classification

Skin Corrosion / Irritation Classification criteria not met

Eye Damage / Irritation Classification criteria not met

Respiratory Irritation Classification criteria not met

Respiratory / Skin Sensitization Classification criteria not met

Germ Cell Mutagenicity Classification criteria not met

Reproductive Toxicity Classification criteria not met

STOT - Single Exposure Classification criteria not met

STOT - Repeated Exposure Classification criteria not met

Aspiration Hazard Classification criteria not met

Carcinogen Data

ID	Calif Prop-65	OSHA	NIOSH	ACGIH	NTP	IARC
6	Yes	-	-	-	-	-
8	Yes	-	-	A3	-	2B

Information on the Likely Routes of Exposure

Routes of Exposure Skin contact, skin absorption, eye contact, inhalation



SAFETY DATA SHEET

TREEKOTE™ Tree Wound Dressing

Part No. E8250CT Aerosol

November 16, 2015

Revision 1

Page 6 of 7

Information on Physical, Chemical and Toxicological Effects

Symptoms of Exposure

Abdominal Cramps, Asphyxia, Bronchitis, Chemical Pneumonitis, Coma, Confusion, Dermatitis, Dizziness, Drowsiness, Excitation, Skin Irritation, Staggering Gait, Throat Irritation, Upper Respiratory System Irritation, Vomiting

Delayed and Immediate Effects and also Chronic Effects from Short and Long-Term Exposure

Delayed Effects

No known delayed effects.

Immediate Effects

No known immediate effects.

Chronic Effects

Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal. Stoddard Solvent when ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction.

Medical Conditions Aggravated

May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

Target Organs

Blood, Central Nervous System, Eyes, Gastrointestinal Tract, Kidneys, Liver, Respiratory System, Skin

SECTION 12 - ECOLOGICAL INFORMATION

Acute Aquatic Toxicity

ID	TYPE	FISH			INVERTEBRATES			AQUATIC PLANTS			MICROORGANISMS		
		VALUE	PERIOD	TYPE	VALUE	PERIOD	TYPE	VALUE	PERIOD	TYPE	VALUE	PERIOD	
1	LC50	125 mg/L	96h	EC50	220 mg/L	48h	—	—	—	—	—	—	
5	LC50	9.22 mg/L	96h	EC50	6.14 mg/L	48h	—	—	—	—	—	—	
6	LC50	4.7 mg/L	96h	EC50	13.7 mg/L	24h	EC50	26 mg/L	72h	EC10	211 mg/L	24h	
7	LC50	26.7 mg/L	96h	LC50	14 mg/L	24h	—	—	—	—	—	—	
8	LC50	97.1 mg/L	96h	LC50	77 mg/L	24h	EC50	63 mg/L	3h	EC50	130 mg/L	48h	

Ecological Data

ID	PERSISTENCE AND DEGRADABILITY				BIOACCUMULATIVE POTENTIAL		MOBILITY Koc
	PERSISTENCE	BOD	COD	ThOD	Pow / Kow	BCF	
1	8% / 28 days	—	—	—	2.09 log Kow	8 BCF	330 Koc
4	—	—	—	—	3.16 log Kow	—	—
5	—	—	—	—	3.714 log Kow	2.12 log BCF	3.4 log Koc
6	—	—	—	—	3.66 log Kow	2.49 log BCF	3.33 log Koc
7	—	0.64 mg/L	—	2410 mg/g	3.271 log Kow	2.2557 log BCF	3.156 log Koc
8	—	1780 mg/g	—	3170 mg/g	3.15 log Kow	1.18 log BCF	2.4 log Koc

Other Adverse Effects

No additional information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal

Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Waste Disposal of Packaging

An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

Landfill Precautions

Not available

Incineration Precautions

** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE **

SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information

UN Number
Proper Shipping Name
Hazard Class(es)
Packaging Group
Marine Pollutant
Hazard Label(s)

Ground Transportation (DOT)

UN1950
 Aerosols, Limited Quantity
 2.1
 —
 No



Air Transportation (IATA)

UN1950
 Aerosols, Flammable, Limited Quantity
 2.1
 —
 No



Ocean Transportation (IMDG)

UN1950
 Aerosols, Limited Quantity
 2.1
 —
 No



SECTION 15 - REGULATORY INFORMATION

Federal Regulations

ID	TSCA LISTED	SARA 302 EHS TPQ	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	SARA 311/312 ACUTE	CHRONIC	PRESSURE	CLEAN AIR ACT HAP	CLEAN WATER ACT SOCMI	CLEAN WATER ACT
1	Yes	Yes	—	—	—	Yes	—	Yes	Yes	—	—	—	>1 (PP)
2	Yes	—	—	—	—	—	—	—	—	—	—	—	—
3	Yes	—	—	—	—	Yes	—	—	—	—	—	—	—
4	Yes	—	—	—	—	—	—	Yes	—	—	—	—	—
5	Yes	—	—	—	2%	Yes	—	Yes	—	—	—	—	—
6	Yes	—	U055	5000	>1%	Yes	—	Yes	—	—	Yes	Yes	—
7	Yes	—	U239	100	>1%	Yes	—	Yes	—	—	Yes	Yes	100
8	Yes	—	—	1000	1%	Yes	—	Yes	—	—	Yes	Yes	1000 (PP)

State Regulations

ID	CA P-65	DE RQ	MA RTK CODES	ME TYPE	ME RQ	RTK	MN AIR	WATER	NJ RTK	AIR	NY LAND	ACUTE	PA LISTED	WA PEL TWA	WI TABLE	WV TAP
1	—	1000	6 F7 F8	—	—	—	—	—	—	1000	1	—	Yes-E	—	—	—
4	—	—	2,4	—	—	ANO	—	—	—	—	—	—	Yes	100 ppm	A	—
5	—	100	F7 F9	—	1000	—	—	—	—	—	—	—	Yes-E	—	—	—
6	C	5000	2,4,5 F7 F8 F9	—	2000	AO	1	—	—	5000	1	—	Yes-E	50 ppm	A	—
7	—	100	2,4 F8 F9	—	2000	ANO	1	—	—	1000	1	—	Yes-E	100 ppm	A	—
8	C	1000	2,4,5,6 F7 F8 F9	—	2000	AO	1	1	—	1000	1	—	Yes-E	100 pp,	A	—

SECTION 16 - OTHER INFORMATION

SDS Revision History

Revision 1, 10/21/2014, Original

SDS Compliance

This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department at msds@chem-pak.com

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200

Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.