# CORPOBION N

#### **SAFETY DATA SHEET**

### **SECTION 1: PRODUCT IDENTIFICATION**

**Product:** Sting Relief Pad

Product Label Name: Sting Relief Pad

Company Name and Address: Dukal Corporation

2 Fleetwood Court

Ronkonkoma, NY 11779

**Emergency Telephone Number**: 631-656-3800

### **SECTION 2: HAZARDOUS IDENTIFICATION**

**Hazard Class/Category:** Flammable Liquid – 3

Eye Irritation - 2B

**Hazard Symbol:** 

Signal Word: Warning

**Hazard Statements:** Flammable liquid and vapor. (H226)

Causes eye irritation. (H320)

**Precautionary statements:** 

**General:** Keep out of reach of children. (P102)

**Eyes:** IF IN EYES: Rinse cautiously with water for several minutes.

If eye irritation persists: Get medical advice/attention.

(P305+P338) (P337+P313)

#### **SECTION 3: INFORMATION ON INGREDIENTS**

Component Name	CAS#	Concentration	R Phrase
Isopropyl Alcohol	67-63-0	60%	R11
Benzocaine	94-09-7	6%	

Chemical Formula: NH2C6H4COOC2H5 / CH3CHOHCH3

# CORPOBION N

#### SAFETY DATA SHEET

#### **SECTION 4: FIRST-AID MEASURES**

#### Emergency first aid procedures by route of exposure:

**Inhalation**: If symptoms are experience, remove source of contamination or move victim to fresh air. If affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

**Ingestion**: Do not induce vomiting. If the material is swallowed have victim drink 1-3 glasses of water to dilute stomach contents. Seek medical attention or advice.

**Skin**: If irritation is experienced, discontinue use. If irritation persists, seek medical attention.

**Eyes**: Rinse eyes with cool water for 15 minutes holding the eye open. Seek medical attention if irritation persists

#### **SECTION 5: FIRE-FIGHTING MEASURES**

Flash Point: 68.5°F, TOC Method

Flammable Limits: 750°F

**Extinguishing Media:** Use methods appropriate for the surrounding fire. Suggested: CO2, dry chemical powder, or alcohol resistant foam.

**Products of Combustion**: Upon decomposition this product may emit carbon dioxide, carbon monoxide and/or low molecular weight hydrocarbons.

**Fire Fighting Equipment/Instructions**: Wear protective clothing and equipment suitable for the surrounding fire, including helmet, facemask, and self contained breathing apparatus.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Personal Precautions**: For large spills wear gloves, safety glasses and when levels exceed OSHA PEL use appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

**Environmental Precautions**: Prevent discharge to open waters.

**Method for Containment**: Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth.

**Methods for Clean-Up**: Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container. Wash spill area with water.

# CORPOBION PARTNERSHIP. POSSIBILITIES.

#### SAFETY DATA SHEET

#### **SECTION 7: HANDLING AND STORAGE**

**Handling**: Keep away from heat, sparks and flame. Prevent contact with eyes. Use in well ventilated area.

**Storage**: Keep the container tightly closed and in a cool, well ventilated place.

#### **SECTION 8: EXPOSURE CONTROLS**

Isopropyl Alcohol (67-63-0)

ACGIH: 200 ppm TWA

**OSHA**: 400 ppm TWA; 980 mg/m3 TWA

Engineering Controls: Normal room ventilation is usually adequate under normal

use.

**Personal Protective Equipment (PPE):** 

**Eye/Face Protection**: None needed under normal use – Wear goggles is exposed

to unusual amount and splashing

**Skin Protection**: None needed under normal use -- Wear overalls or apron if

splashing is possible

**Respiratory Protection**: May be needed if vapor concentrations are high.

**General Hygiene Considerations**: None needed under normal use.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State: Individually sealed Sting Relief Packet. Packet may contain some free liquid.

Appearance/Color: White Non-Woven cloth saturated with clear solution

Odor: Alcohol PH: Not Available.

Vapor Pressure: Unknown

Flammability Properties (see section 5)

Solubility (in water): Chemical Is Soluble, Pad Not Soluble

Specific Gravity @ 25°C: 0.8405 Evaporation Rate: Not Available

**Auto-ignition temperature**: Not Available **Decomposition temperature**: Not Available

#### **SECTION 10: STABILITY AND REACTIVITY**

**Stability**: Stable under normal ambient temperatures 70°C (21°C) **Condition to Avoid**: Avoid excessive heat or sources of ignition.

Incompatible Materials: This product reacts with strong acid, strong bases, and oxidizing agents.

Hazardous Decomposition: Unknown

Hazardous Reactions: Hazardous polymerization will not occur.

**OSHA Standard Format** 

# CORPOBION N

#### SAFETY DATA SHEET

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### **ACUTE EFFECTS**:

A: General Product information

Product contains isopropyl alcohol.

**B: Acute Toxicity** 

Low order of acute toxicity is possible.

**CHRONIC EFFECTS**: Component

Isopropyl Alcohol (67-63-0) -- This product is not expected to cause long term adverse effects

Carcinogenicity: Not Classifiable as a Human Carcinogen

**Reproductive**: This product is not expected to cause reproductive health effects **Developmental**: This product is not expected to cause reproductive health effects.

Target Organs: When consumed, isopropyl alcohol can target the respiratory system, skin, eyes,

CNS, liver, blood and reproductive system.

#### **SECTION 12: ECOLOGICAL INFORMATION**

Mixtures of alcohols are toxic to aquatic life at moderate to low concentrations. No long-term ecological effects are likely. Concentrated solutions of alcohols and surfactants may cause damage to aquatic and terrestrial plants.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose in accordance with federal state and local regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld near container. Do not incinerate closed containers. Empty containers may contain hazardous residues. Dispose of containers with care.

#### **SECTION 14: TRANSPORATION INFORMATION**

**Note:** Individually sealed packet may contain some free liquid.

**DOT** (ORM-D Exemption) **Proper Shipping Name** ISOPROPANOL

Hazard Class 3
Packing Group ||

**Description** CONSUMER COMMODITY/ LTD QTY, ORM-D

Emergency Response Guide Number 127

<u>UN-No</u>. UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3
Packing Group | |

Description UN1219, ISOPROPANOL, 3, II

Limited Quantity 1 Liter

### CORPOBION

#### SAFETY DATA SHEET

**IATA** 

PASSION. PARTNERSHIP. POSSIBILITIES

**UN-No.** UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3
Packing Group ||

**Description** UN1219, ISOPROPANOL, 3, II

Marine Pollutant NO

IMDG/IMO

**UN-No.** UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3
Packing Group ||

**EMS No.** F-E, S-D

**Description** UN1219, ISOPROPANOL, 3, II, (23°C C.C.)

Marine Pollutant NC

**DOT Ground ORM-D:** ORM-D Exemption:

ORM-D (Other Regulated Material – Domestic): Consumer Commodity, Limited Quantity.

"ORM-D, Consumer Commodity" label for domestic ground shipping in consumer packaging only. Suitable ORM-D labelling for air and vessel shipments requires additional labelling and Shipping Papers, in accordance with DOT CFR 172.

"Limited Quantity" marking required on each package for ground shipping of limited quantities (1 Liter or less) without Shipping Papers, as defined in DOT CFR 172.101.

### **SECTION 15: REGULATORY INFORMATION**

**DOT/USA** 

**Label Information:** Flammable Liquid

WHMIS / CANADA

Class: B2 Flammable Liquid

#### **SECTION 16: OTHER INFORMATION**

Issue Date: 03-26-2014 Revision Date: 07-01-2016

#### **Disclaimer:**

The information provided in this SDS is correct and is to the best of our knowledge, at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**OSHA Standard Format**