

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: UNIVERSAL POLYPROPYLENE ABSORBENTS

PRODUCT USE: SORBENT MEDIA USED TO ABSORB LEAKS AND SPILLS WHICH INCLUDE BUT NOT LIMITED TO OIL, WATER,

COOLANTS AND SOLVENTS

SPECIFIC PRODUCT TYPE: ABSORBENT PADS

COMPANY INFORMATION: ENPAC, LLC PHONE: 440-975-0070

 34355 MELINZ DRIVE
 FAX:
 440-975-0047

 EASTLAKE, OH 44095
 EMER:
 440-975-0070

SECTION 2: HAZARDS IDENTIFICATION

THIS PRODUCT IS NOT DANGEROUS IN ITS UNUSED FORM AND CONTAINS NO HAZARDOUS INGREDIENTS. NOT WHMIS REGULATED.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

MATERIALS	PERCENT	CAS#
POLYPROPYLENE:	>97%	9003-07-0
SURFACTANT:	< 1%	9004-34-6
GRAY PIGMENT	< 1%	NONE
YELLOW PIGMENT	< 1%	NONE
GREEN PIGMENT	< 1%	NONE
ORANGE PIGMENT	< 1%	NONE

SECTION 4: FIRST AID MEASURES

NO SPECIAL PROCEDURES REQUIRED

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >315 DEGREES CELCIUS (ASTM D93)

FLAMMABLE LIMITS: NOT YET DETERMINED

EXTINGUISHING MEDIA: WATER, FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: STANDARD PROCEDURE FOR CLASS A FIRES

UNUSUAL FIRE AND EXPLOSION HAZARD: SOME CARBON MONOXIDE UNDER LEAN OXYGEN CONDITIONS

SECTION 6: ACCIDENTAL RELEASE MEASURES

NO SPECIAL STEPS ARE TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

SECTION 7: HANDLING AND STORAGE

STORE IN DRY AREA. DO NOT STORE NEAR OPEN FLAME, HIGH HEAT OR STRONG OXIDANTS. POLYPROPYLENE, WHEN HEATED, BECOMES VERY STICKY AND WILL BURN. USE SELF-CONTAINED AIR MASK TO ENTER SMOKY AREA IN THE EVENT OF FIRE.

SECTION 8: EXPOSUR CONTROLS/PERSONAL PROTECTIVE EQUIPMENT EXPOSURE LIMITS: OSHA PEL: N/A ACGIH TLV: N/A

RESPIRATORY PROTECTION:

VENTILATION:

NONE REQUIRED

NONE REQUIRED

PROTECTIVE GLOVES: NONE REQUIRED ONLY IF MOLTAN

EYE PROTECTION:

OTHER PROTECTIVE EQUIPMENT (SPECIFY):

NONE REQUIRED

NONE REQUIRED

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

COLOR: GRAY, YELLOW, GREEN, ORANGE

DENSITY: 0.04 - 0.06 gram/cc

ODOR: CITRUS (IN ORANGE ABSORBENT)

SPECIFIC GRAVITY: 0.88 - 0.92

FLASH POINT: NOT APPLICABLE

BOILING POINT: NOT APPLICABLE

MELTING POINT: > 160 DEGREES CELSIUS

SOLUBILITY IN WATER: INSOLUBLE
PERCENT VOLATILE: NOT APPLICABLE
EVAPORATION RATE: NOT APPLICABLE
VAPOR PRESSURE (mm Hg): NOT APPLICABLE
VAPOR DENSITY (Air = 1): NOT APPLICABLE

AUTO IGNITION TEMPERATURE >675 DEGREES FAHRENHEIT

SECTION 10: STABILITY AND REACTIVITY DATA

STABILITY: STABLE INCOMPATIBILITY (conditions to avoid): NONE

INCOMPATIBILITY (materials to avoid): NITRIC ACID, PERCHLORIC ACID, SULFURIC ACID OR 98% SULFURIC ACID

HAZARDOUS DECOMPOSITON: WHEN HEATED, IT MAY EMIT TOXIC

HAZARDOUS POLYMERAZATION: WILL NOT OCCUR

SECTION 11: TOXOCOLOGICAL INFORMATION

HEALTH HAZARDS (acute or cronic):

SIGNS OR SYSMPTOMS OF EXPOSURE:

MEDICAL CONDITIONS GENERRALLY AGGRAVATED BY EXPOSURE:

NONE

DATE ISSUED: January 1, 2018
PREPARED BY: ENPAC, LLC

SECTION 12 TO SECTION 15 NOT APPLICABLE

SECTION 16: OTHER INFORMATION

SDS PREPARATION DATE: January 1, 2018

THE INFORMATION CONTAINED HEREIN IS ACCCURATE TO THE BEST OF MY KNOWLEDGE. MY COMPANY MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE SAFE USE OF THIS MATERIAL IN YOUR PROCESS OR IN COMBINATION WITH OTHER SUBSTANCES



SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: OIL ONLY POLYPROPYLENE ABSORBENTS

PRODUCT USE: SORBENT MEDIA USED TO ABSORB OIL-BASED CHEMICALS WHICH INCLUDE BUT NOT LIMITED TO DIESEL FUEL, OIL, GASOLINE

AND KEROSENE WHILE REPELLING WATER AND WATER BASED PRODUCTS.

SPECIFIC PRODUCT TYPE: ABSORBENT PADS

COMPANY INFORMATION: ENPAC, LLC PHONE: 440-975-0070

34355 MELINZ DRIVE FAX: 440-975-0047 EASTLAKE, OH 44095 EMER: 440-975-0070

SECTION 2: HAZARDS IDENTIFICATION

THIS PRODUCT IS NOT DANGEROUS IN ITS UNUSED FORM AND CONTAINS NO HAZARDOUS INGREDIENTS. NOT WHMIS REGULATED.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

MATERIALS	PERCENT	CAS#
POLYPROPYLENE:	>97%	9003-07-0
ANTI STATIC AGENT	<0.3%	NONE
WHITE PIGMENT	< 1%	NONE
PINK PIGMENT	<1%	NONE
BLUE PIGMENT	< 1%	NONE

SECTION 4: FIRST AID MEASURES

NO SPECIAL PROCEDURES REQUIRED

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >315 DEGREES CELCIUS (ASTM D93)

FLAMMABLE LIMITS: NOT YET DETERMINED

EXTINGUISHING MEDIA: WATER, FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: STANDARD PROCEDURE FOR CLASS A FIRES

UNUSUAL FIRE AND EXPLOSION HAZARD: SOME CARBON MONOXIDE UNDER LEAN OXYGEN CONDITIONS

SECTION 6: ACCIDENTAL RELEASE MEASURES

NO SPECIAL STEPS ARE TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

SECTION 7: HANDLING AND STORAGE

STORE IN DRY AREA. DO NOT STORE NEAR OPEN FLAME, HIGH HEAT OR STRONG OXIDANTS. POLYPROPYLENE, WHEN HEATED, BECOMES VERY STICKY AND WILL BURN. USE SELF-CONTAINED AIR MASK TO ENTER SMOKY AREA IN THE EVENT OF FIRE

SECTION 8: EXPOSUR CONTROLS/PERSONAL PROTECTIVE EQUIPMENT EXPOSURE LIMITS: OSHA PEL: N/A ACGIH TLV: N/A

RESPIRATORY PROTECTION:

VENTILATION:

NONE REQUIRED

NONE REQUIRED

PROTECTIVE GLOVES:NONE REQUIRED
ONLY IF MOLTAN

EYE PROTECTION: NONE REQUIRED
OTHER PROTECTIVE EQUIPMENT (SPECIFY): NONE REQUIRED

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

COLOR: WHITE, BLUE

DENSITY: 0.04 - 0.06 gram/cc

ODOR: NO ODOR

SPECIFIC GRAVITY: 0.88 - 0.92

FLASH POINT: NOT APPLICABLE

BOILING POINT: NOT APPLICABLE

MELTING POINT: > 160 DEGREES CELSIUS

SOLUBILITY IN WATER: INSOLUABLE

PERCENT VOLATILE: NOT APPLICABLE
EVAPORATION RATE: NOT APPLICABLE
VAPOR PRESSURE (mm Hg): NOT APPLICABLE
VAPOR DENSITY (Air = 1): NOT APPLICABLE

AUTO IGNITION TEMPERATURE >675 DEGREES FAHRENHEIT

SECTION 10: STABILITY AND REACTIVITY DATA

STABLEITY: STABLE INCOMPATIBILITY (conditions to avoid): NONE

INCOMPATIBILITY (materials to avoid): NITRIC ACID, PERCHLORIC ACID, SULFURIC ACID OR 98% SULFURIC ACID

HAZARDOUS DECOMPOSITON: WHEN HEATED, IT MAY EMIT TOXIC

HAZARDOUS POLYMERAZATION: WILL NOT OCCUR

SECTION 11: TOXOCOLOGICAL INFORMATION

HEALTH HAZARDS (acute or cronic):

SIGNS OR SYSMPTOMS OF EXPOSURE:

MEDICAL CONDITIONS GENERRALLY AGGRAVATED BY EXPOSURE:

NONE

DATE ISSUED: 1/1/2018
PREPARED BY: ENPAC, LLC

SECTION 12 TO SECTION 15 NOT APPLICABLE

SECTION 16: OTHER INFORMATION

SDS PREPARATION DATE: January 1, 2018

THE INFORMATION CONTAINED HEREIN IS ACCCURATE TO THE BEST OF MY KNOWLEDGE. MY COMPANY MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE SAFE USE OF THIS MATERIAL IN YOUR PROCESS O IN COMBINATION WITH OTHER SUBSTANCES



SAFETY DATA SHEET — 16 Sections

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION [WHMIS Classification] Perlite, Expanded, ENSORB Super Absorbent Not Applicable Product Use Industrial Absorbent Manufactured For: ENPAC, LLC Street Address 34355 Melinz Parkway City, State, Postal Code Eastlake, Ohio 44095 Emergency Telephone 440-975-0070 Date SDS Prepared 1/1/2018 SECTION 2 — HAZARDS IDENTIFICATION Route of Entry Skin Contact ☐ Skin Absorption ☐ Eye Contact ☐ Inhalation ☐ Ingestion **Emergency Overview** This product contains crystalline silica (less than .01%). OSHA considers perlite to be a nuisance dust. Inhalation of high amounts over long periods of nuisance dust may overload lung clearance mechanism and make the lungs more vulnerable to respiratory disease. WHMIS Symbols Not Regulated Potential Health Effects Inhalation: Pre-existing upper respiratory and lung disease may be aggravated. Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Chronic inhalation of dust should be avoided. Eye: May cause irritation (tear formation and redness) if dust gets in eyes. Skin: Not absorbed by the skin. But may cause dryness if prolonged exposure. Ingestion: Ingestion of small to moderate quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients (specific)	%	CAS Number	LD 50 of Ingredient (specify species and route)	LC 50 of Ingredient (specify species)	OSHA PEL (mg/m3)	ACGIH TLV (mg/m3)
Perlite	100	93763-70-3	Not Available	Not Available	10	15
Silica/ Quartz	< 0.1	14808-60-7	Not Available	Not Available	Not Available	.05



SECTION 4 — FIRST AID MEASURES

Skin Contact
Use moisture renewing lotions if dryness occurs.
Eye Contact
Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.
Inhalation
Remove to fresh air. Blow nose to evacuate dust.
Ingestion
Drink generous amounts of water to reduce bulk and drying effects.

SECTION 5 — FIRE FIGHTING MEASURES

C=:		
Flammable	If yes, under which conditions?	
□ _{Yes} □ _{No}		
Means of Extinction		
N/A		
Flashpoint (° C) and Method	Upper Flammable Limit (% by volume)	Lower Flammable Limit (% by volume)
None	None	None
Auto ignition Temperature (°C)	Explosion Data — Sensitivity to Impact	Explosion Data — Sensitivity to Static Discharge
Not Combustible	N/A	N/A
Hazardous Combustion Products		
N/A		
NFPA		
N/A		

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal Precautions: If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles.

Containment and Cleanup: Vacuum clean dust with equipment fitted with HEPA filter. Use dust suppressant such as water if sweeping is necessary.

Environment: Not considered as hazardous waste by RCRA (40 CFR Part 261). Place waste and spillage in closed containers. Dispose of in approved landfill.

SECTION 7 — HANDLING AND STORAGE

Handling Procedures and Equipment
Minimize dust generation. Avoid contact with eyes. Avoid breathing dust. Repair or dispose of broken bags.
Storage Requirements
Store in a dry place to maintain packaging integrity and product quality. Do not store near hydrofluoric acid. Observe all label
precautions and warnings.



SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

	X ACGIH TLV	⊠OSHA PEL	Other (spec	cify)		
Specific Engineering Controls (such as ventilation, enclosed process)						
Adequate ventilation and appropriate local exhaust where needed to keep dust level below PEL.						
Personal Protective Equipment	Gloves	Respirator	Eye	Footwear	Clothing	Other
If checked, please specify type						
Eye: Goggles to protect	ct from dust.					
Skin: No special equipment is required.						
Respiratory: Respirators fitted with filters certified to standard 42CFR84 under series N95 should be worn when dust is present. If the dust concentration is less than ten (10) time the Permissible Exposure Limit (PEL) use a quarter or half mask respirator. If dust concentration is greater than ten (10) times and less than fifty (50) times the PEL, a full-face piece respirator fitted with replaceable N95 filters is recommended. If dust concentration is greater than fifty (50) and less than two-hundred (200) times the PEL use a power air-purify (positive pressure) respirator with replaceable N95 filter. If dust concentration is greater than two-hundred (200) times the PEL use a type C, supplied air respirator (continuous flow, positive pressure), with						

full face piece, hood or helmet.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Odor and Appearance	Odor Threshold (ppm)
Solid	White Granules or Powder. No distinct	N/A
	odor.	
Specific Gravity	Vapor Density (air = 1)	Vapor Pressure (mmHg)
2.35	N/A	N/A
Evaporation Rate	Boiling Point (° C)	Freezing Point (° C)
N/A	N/A	N/A
рН	Coefficient of Water/Oil Distribution	[Solubility in Water]
6-10	N/A	Slightly Soluble



SECTION 10 — STABILITY AND REACTIVITY

Chemical Stability			If no, under which conditions?		
	⊠ _{Yes}	\square No			
Incompatibility with Ot			If yes, which ones?		
	⊠Y e s	□No	Reacts with Hydrofluoric	Acid to form Silicon Tetrafluoride gas	
Reactivity and under	what conditions?				
_	s reactions know	'n.			
Hazardous Decomp	osition Products				
None					
SECTION Effects of Acute Ex		OLOGIC	AL INFORMATION		
Potential irri	tant for skin cont	act, eve cor	tact or inhalation.		
		, - ,			
Effects of chronic e	exposure				
Perlite is a naturally occurring volcanic glass consisting of fused sodium-potassium-aluminum silicate. Tests conducted on Perlite have not identified crystalline silica as being present above the detection limit (0.05%). Although there are not published reports of adverse health effects from exposure to perlite dust, dust levels should be maintained below the OSHA Permissible Exposure Limit for perlite and respirators used when airborne dust is present.					
Irritancy of Product					
Potential irri	tant for skin cont	act, eye cor	tact or inhalation.		
Skin sensitization	Skin sensitization Respiratory sensitization				
	ough skin contac	t.			
Carcinogenicity-IA	RC		Ca	rcinogenicity - ACGIH	
N/A N/A					
Reproductive toxicity Teratogenicity					
N/A			N	'A	
Embrotoxicity			Mu	tagenicity	
N/A			N	'A	
Name of synergistic products/effects					
N/A	N/A				

SECTION 12 — ECOLOGICAL INFORMATION

SECTION 12 — ECOLOGICAL INFORMATION				
Aquatic Toxicity				
Generally considered inert. Perlite has no negative ecological effect and may be used as a soil container.				
SECTION 13 — DISPOSAL CONSIDERATIONS				
Waste Disposal				
Not considered hazardous waste by the RCRA (40 CFR Part	261). Place waste and spillage in	closed containers.		
Dispose in accordance with Federal, State and Local regulation	ons.			
SECTION 14 — TRANSPORT INFORMATION Special Shipping Information				
No known shipping regulations.		500		
		PIN NI/A		
TDG		N/A		
N/A	N/A			
IMO	ICAO			
N/A	N/A			
SECTION 15 — REGULATORY INFORMATION WHMIS Classification	OSHA			
Not regulated	Perlite is not considered as a toxic	or hazardous subject.		
SERA National	TSCA			
Not Listed	Not Listed.			
This product has been classified in ac Controlled Products Regulations (CPR) and the S				
SECTION 16 — OTHER INFORMATION				
Notice: This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. All statements, information and data provided are believed to be accurate and				
reliable, but are presented without any guarantee, representation, warranty or responsibility of any kind, expressed or				
implied. Any and all representations and/or warranties of merchantability of fitness for a particular purpose are specifically				
disclaimed. Users should make their own investigations as to the suitability of the information or product for their particular				
purpose. Nothing in this document is intended as permission, inducement or recommendation to violate any laws or practice any invention covered by existing patents, copyrights or inventions. ENPAC,LLC. does not accept liability for any loss or				
damage that may occur from the use of this information.				