Identification

Page E1 of E2

Innovating Science by Aldon Corporation "cutting edge science for the classroom"

221 Rochester Street Avon, NY 14414-9409 (585) 226-6177 CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

Product	HYDROCHLORIC ACID, 1 MOLAR (1 NORMAL) SOLUTION
---------	--

Synonyms Muriatic Acid, Water Solution / Hydrogen Chloride, Water Solution

Section 2 Hazards identification

Signal word: WARNING Pictograms: GHS05

Target organs: Respiratory system, skin, eyes, lungs.



GHS Classification:

Corrosive to metals (Category 1) Skin irritant (Category 3) Eye irritant (Category 2B)

GHS Label information: Hazard statement(s):

H290: May be corrosive to metals. H316: Causes mild skin irritation. H320: Causes eye irritation.

Precautionary statement(s):

P234: Keep only in original container. P264: Wash hands thoroughly after handling.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313: If skin irritation occurs: Get medical attention.

P337+P313: If eye irritation persists: Get medical attention. P390: Absorb spillage to prevent material damage.

P406: Store in corrosive resistant container with a resistant inner liner.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / ir	formation on ingredients		
Chemical Name	CAS#	%	EINECS
Water Hydrochloric acid	7732-18-5 7647-01-0	96.86% 3.14%	231-791-2 231-595-7

Section 4 First aid measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: MAY CAUSE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY CAUSE IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Contact with metals produce hydrogen, which is flammable and may produce explosive mixtures with air.

Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, well-ventilated area away from incompatible substances.

Section 8	Exposure controls / personal	protection		
E	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
Exposure Limits:	Hydrogen chloride	STEL: C 2 ppm / C 2.98 mg/m ³	STEL: C 5 ppm / C 7 mg/m ³	STEL: C 5 ppm / C 7 mg/m ³

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low. Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Physical and chemical properties Section 9

Appearance: Clear, colorless liquid.

Odor: No odor.
Odor threshold: No data available

No data available

Melting / Freezing point: ~ 0°C (~ 32°F) [water] Boiling point: ~ 100°C (212°F) [water]

Flash point: Not flammable. Evaporation rate (= 1): < 1

Flammability (solid/gas): No data available Explosion limits: Upper/Lower: No data available Vapor pressure (mm Hg): 14 [water] Vapor density (Air = 1): 0.7 [water]

Relative density (Specific gravity): 1.0 [water]
Solubility(ies): Complete.
Partition coefficient: (n-octanol / water): No data available Auto-ignition temperature: No data available

Decomposition temperature: No data available

Viscosity: No data available Molecular formula: Mixture. Molecular weight: Mixture.

Section 10

Stability and reactivity

Hazardous polymerization: Will not occur. Chemical stability: Stable

Conditions to avoid: Containers may burst when heated. Avoid contact with water.

Incompatible materials: Metals, bases, active metals, alkali metals, oxidizing agents, hydroxides, amines, carbonates, cyanides, sulfides, sulfites,

formaldehyde.

Hazardous decomposition products: Hydrogen chloride gas.

Toxicological information Section 11

Acute toxicity: Data not available

Skin corrosion/irritation: Data not available at this dilution. Serious eye damage/irritation: Data not available at this dilution.

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by NTP.

IARC: Group 3: Not classifiable as to its carcinogenicity to humans.

OSHA. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Ca Prop 65: This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

Reproductive toxicity: Data not available

STOT-single exposure: Data not available at this dilution.

STOT-repeated exposure: Data not available

Aspiration hazard: Data not available

Potential health effects: To the best of our knowledge the chemical, physical and toxicological properties have not been thoroughly investigated. Specific data is not available.

Exercise appropriate procedures to minimize potential hazards.

Inhalation: May be harmful if inhaled. Material may cause irritation to the tissue of the mucous membranes and upper respiratory tract.

Ingestion: May be harmful if swallowed. Skin: May cause irritation and/or burns. Eyes: May cause irritation and/or burns.

Signs and symptoms of exposure: Data not available at this dilution. Additional information: RTECS #: MW4025000 [Hydrochloric acid]

Ecological information

Toxicity to fish: LC50 - Gambusia affinis (Mosquito fish) - 282 mg/l - 96 h (Hydrochloric acid)

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available

Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Transport information Section 14

UN/NA number: UN1789 Shipping name: Hydrochloric acid

Reportable Quantity: 5000 lbs (2270 kg) Marine pollutant: No Hazard class: 8 Packing group: III

2020 FRG Guide # 157 Exceptions: Limited quantity equal to or less than 5 Lt

Regulatory information Section 15

A chemical is considered to be listed if the CAS number for the aphydrous form is on the Inventory list

TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Listed	5000 lbs (2270 kg)	D002	Listed	Not listed	This product does not contain any chemicals known to the State of California to cause cancer or
					1331 33131 4131

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent dent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure ERG: Emergency Response Guidebook.

Form 06/2015

Revision Date: October 1, 2020

Supercedes: December 27, 2019

Identification

Page E1 of E2

Innovating Science® by Aldon Corporation

Hazards identification

"cutting edge science for the classroom"

221 Rochester Street Avon, NY 14414-9409 (585) 226-6177 CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

Product CALCIUM SULFATE, HEMIHYDRATE

Synonyms Plaster of Paris / Dried Gypsum

Signal word: WARNING Pictograms: GHS08 Target organs: None known



GHS Classification: *STOT-RE (Category 2)

GHS Label information: Hazard statement:

*H373: May cause damage to organs (*lungs*) through prolonged or repeated exposure (*inhalation*).

* Respirable dust particles containing crystalline silica may be generated by crushing. There are no known hazards associated with this material when used as recommended.

Precautionary statement:

P260: Do not breathe dust.

P314: Get medical advice/attention if you feel unwell.

P501; Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Chemical Name	CAS#	%	EINECS
Calcium sulfate, hemihydrate Calcium carbonate Crystalline silica	26499-65-0 1317-65-3 14808-60-7	60-100% 10-30% 0.5-1.5%	231-900-3 (anhydrous) 215-279-6 238-878-4

Section 4 First aid measures

INGESTION: Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: PROLONGED INHALATION OF PARTICULATE DUST MAY BE HARMFUL. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: MAY CAUSE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY CAUSE ABRASIONS. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Product will not burn or support fire. Use any media suitable for extinguishing supporting fire

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: Limestone reacts with acids to release carbon dioxide.

Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Do not inhale dusts. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area.

Section 8	Exposure controls / personal protect	tion		
Evnosuro Limite:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
Exposure Limits:	Calcium sulfate	TWA: 10 I mg/m ³	TWA: 5 mg/m ³ Respirable fraction	TWA: 5 mg/m ³ Respirable fraction

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator

Physical and chemical properties

Appearance: Solid. White powder.

Odor: No odor

Odor threshold: Data not available.

pH: Data not available

Melting / Freezing point: Data not available

Boiling point: Data not available Flash point: Not flammable

Evaporation rate (= 1): Not applicable Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: Not flammable Vapor pressure (mm Hg): Data not available Vapor density (Air = 1): Data not available Relative density (Specific gravity): 2.8

Solubility(ies): Data not available

Partition coefficient: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: Data not available Viscosity: Data not available

Molecular formula: CaSO₄•1/2H₂O Molecular weight: 145.15

Section 10 Stability and reactivity

Chemical stability: Stable

Hazardous polymerization: Will not occur.

Conditions to avoid: Avoid contact with acids.

Incompatible materials: Strong oxidizers, bases. Reacts with acids to liberate carbon dioxide.

Hazardous decomposition products: Carbon oxides, nitrogen oxides.

Toxicological information

Acute toxicity: Data not available

Skin corrosion/irritation: Data not available Serious eye damage/irritation: Data not available Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: Known to be a human carcinogen (respirable). [crystalline silica]* IARC classified: Group 1: Carcinogenic to humans. [crystalline silica]*

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. Ca Prop 65: A WARNING! This product can expose you to a chemical, crystalline silica, which is known to the State of California to cause cancer.

Reproductive toxicity: Data not available STOT-single exposure: Data not available

STOT-repeated exposure: Inhalation - May cause damage to organs through prolonged or repeated exposure. [crystalline silica]*

Aspiration hazard: Data not available

Potential health effects:

Inhalation: May cause irritation to the respiratory tract (nose, mouth, mucous membranes).

Ingestion: Harmful if swallowed. May cause irritation to mucous membranes. May result in obstruction when material hardens.

Skin: May cause irritation and/or dry skin. May develop enough heat to cause burns if a large mass is kept in contact with skin while hardening (such as casts).

Eves: May cause irritation.

Signs and symptoms of exposure: Prolonged inhalation of particulate dust, may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. Additional information: RTECS #: TP0700000

* Respirable dust particles containing crystalline silica may be generated by crushing. There are no known hazards associated with this material when used as recommended.

Ecological information

Toxicity to fish: No data available

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available Mobility in soil: No data available

Persistence and degradability: No data available

Bioaccumulative potential: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: Not applicable Hazard class: Not applicable Exceptions: Not applicable

Shipping name: Not Regulated Packing group: Not applicable

Reportable Quantity: No

Marine pollutant: No

2020 ERG Guide # Not applicable Regulatory information Section 15

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Calcium sulfate, anhydrous	Listed	Not listed	Not listed	Listed	Not listed	

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Form 06/2015

Revision Date: September 22, 2020 Supercedes: October 23, 2019

Identification

Page E1 of E2

Innovating Science® by Aldon Corporation

"cutting edge science for the classroom"

Avon NY 14414-9409 (585) 226-6177

CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

LIMESTONE Product Calcium Carbonate Synonyms

Hazards identification Section 2

Signal word: WARNING Pictograms: GHS08 Target organs: None known



GHS Classification:

*STOT-RE (Category 2)

GHS Label information: Hazard statement:

*H373: May cause damage to organs (lungs) through prolonged or repeated exposure (inhalation).

* Respirable dust particles containing crystalline silica may be generated by crushing. There are no known hazards associated with this material when used as recommended.

Precautionary statement:

P260: Do not breathe dust.

P314: Get medical attention if you feel unwell.

P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Chemical Name	CAS#	%	EINECS	
Limestone (Calcium carbonate) Quartz	1317-65-3 14808-60-7	≥99% 0.1-1.0%	215-279-6 238-878-4	
		- 10 16.0		
	THE RESERVE OF THE PARTY OF			

First aid measures Section 4

INGESTION: Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: PROLONGED INHALATION OF PARTICULATE DUST MAY BE HARMFUL. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: MAY CAUSE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Fire fighting measures

Suitable Extinguishing Media: Product will not burn or support fire. Use any media suitable for extinguishing supporting fire

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: Limestone reacts with acids to release carbon dioxide

Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Do not inhale dusts. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area.

Section 8	Exposure controls / personal p	rotection		
	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
Exposure Limits:	Silica, crystalline, α-quartz	TWA: 0.025 mg/m ³ respirable (A2)	TWA: 10 mg/m ³ respirable dust	TWA: 0.05 mg/m ³ respirable dust

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator

Physical and chemical properties Section 9

Appearance: Solid. Tan to light brown round particles.

Odor: No odor

Odor threshold: Data not available.

pH: Data not available

Melting / Freezing point: Data not available

Boiling point: Data not available Flash point: Not flammable

Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: Not flammable Vapor pressure (mm Hg): Data not available Vapor density (Air = 1): Data not available

Relative density (Specific gravity): 2.6 - 2.75 Solubility(ies): Insoluble in water.

Evaporation rate (= 1): Not applicable

Partition coefficient: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: Data not available.

Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture

Section 10 Stability and reactivity

Hazardous polymerization: Will not occur. Chemical stability: Stable

Conditions to avoid: Avoid contact with incompatible materials.

Incompatible materials: Contact with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide and oxygen difluoride may cause fire.

Hazardous decomposition products: Will dissolve in hydrofluoric acid and produce silicon tetrafluoride, a corrosive gas.

Toxicological information Section 11

Acute toxicity: Data not available

Skin corrosion/irritation: Data not available Serious eye damage/irritation: Data not available Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: Known to be a human carcinogen (respirable). [crystalline silica]* IARC classified: Group 1: Carcinogenic to humans. [crystalline silica]*

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. Ca Prop 65: A WARNING! This product can expose you to a chemical, crystalline silica, which is known to the State of California to cause cancer.

Reproductive toxicity: Data not available STOT-single exposure: Data not available

STOT-repeated exposure: Inhalation - May cause damage to organs through prolonged or repeated exposure. [crystalline silica]*

Aspiration hazard: Data not available

Potential health effects:

Inhalation: Dust may cause congestion and irritation in nasal and respiratory passages.

Ingestion: Ingestion may cause gastrointestinal irritation and blockage.

Skin: May cause abrasions.

Eyes: May cause mild to severe irritation by abrasion with dust or chips.

Signs and symptoms of exposure: Prolonged inhalation of particulate dust, may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. Additional information: RTECS #: EV9580000 * Respirable dust particles containing crystalline silica may be generated by crushing. There are no known hazards associated with this material when used as recommended.

Ecological information

Toxicity to fish: No data available

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available

Persistence and degradability: No data available Mobility in soil: No data available

Bioaccumulative potential: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Transport information Section 14

UN/NA number: Not applicable Hazard class: Not applicable

Shipping name: Not Regulated

Packing group: Not applicable 2020 ERG Guide # Not applicable

Reportable Quantity: No

Marine pollutant: No

Exceptions: Not applicable Section 15 Regulatory information

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Limestone	Listed	Not listed	Not listed	Listed	Not listed	

Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent of the safety and health of employees. NTP: National Toxicology Program, dent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicolog IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Expo ERG: Emergency Response Guidebook

Form 06/2015

Revision Date: October 6, 2020

Supercedes: February 1, 2019

Identification

Page E1 of E2

Innovating Science® by Aldon Corporation "cutting edge science for the classroom"

on Corporation 221 Rochester Street Avon, NY 14414-9409 (585) 226-6177 CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

Product GRANITE
Synonyms Crushed Stone

Section 2 Hazards identification

Signal word: WARNING Pictograms: GHS08

Target organs: Central nervous system, Respiratory system, Eyes, Skin



GHS Classification: *STOT-RE (Category 2)

GHS Label information: Hazard statement:

*H373: May cause damage to organs (*lungs*) through prolonged or repeated exposure (*inhalation*).

* Respirable dust particles containing silicon dioxide may be generated by crushing. There are no known hazards associated with this material when used as recommended.

Precautionary statement:

P260: Do not breathe dust.

P314: Get medical advice/attention if you feel unwell.

P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Chemical Name	CAS#	%	EINECS	
Silicon dioxide	14808-60-7	70-72%	231-545-4	
Aluminum oxide	1344-28-1	13-15%	None assigned	
Potassium oxide	12136-45-7	4-5%	None assigned	
Sodium oxide	1313-59-3	3-4%	235-641-7	
erric oxide	1309-37-1	1-2%	None assigned	
errous oxide	1345-25-1	1-2%	None assigned	
Calcium oxide	1305-78-8	1-2%	215-138-9	
Magnesium oxide	1309-48-4	<1%	215-171-9	

Section 4 First aid measures

INGESTION: Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: PROLONGED INHALATION OF PARTICULATE DUST MAY BE HARMFUL. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: MAY CAUSE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY CAUSE ABRASIONS. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Product will not burn or support fire. Use any media suitable for extinguishing supporting fire

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool..

Specific Hazards: None known.

Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Section 7 Handling and storage

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Do not inhale dusts. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area.

Section 8	Exposure controls / personal pro	tection		
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
Exposure Limits.	Particles not otherwise classified	TWA: 5 mg/m ³ respirable fraction	None established	None established

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Section 9 Physical and chemical properties

Appearance: Solid. Red, white, black, tan angular pieces.

Odor: No odor.

Odor threshold: Data not available.

pH: Data not available.

Melting / Freezing point: Data not available

Boiling point: Data not available Flash point: Not flammable

Evaporation rate (= 1): Not applicable Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: Not flammable Vapor pressure (mm Hg): Data not available Vapor density (Air = 1): Data not available Relative density (Specific gravity): 2.6-2.81

Solubility(ies): Insoluble in water

Partition coefficient: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: Data not available.

Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur.

Conditions to avoid: Contact with incompatible materials.

Incompatible materials: Strong oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride and oxygen difluoride may cause fire and/or explosion. Silica dissolves in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride.

Hazardous decomposition products: Silica containing respirable dust particles may be generated by handling. When heated, quartz is slowly transformed into tridymite (>860°C/1580°F) and cristobalite (>1470°/2678°F).

Section 11 Toxicological information

Acute toxicity: Data not available

Skin corrosion/irritation: Data not available Serious eye damage/irritation: Data not available Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available Carcinogenity: Data not available

NTP: Known to be a human carcinogen (respirable). [crystalline silica]

IARC classified: Group 1: Carcinogenic to humans. [crystalline silica]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. Ca Prop 65: A WARNING! This product can expose you to a chemical, crystalline silica, which is known to the State of California to cause cancer.

Reproductive toxicity: Data not available STOT-single exposure: Data not available

STOT-repeated exposure: Inhalation - May cause damage to organs through prolonged or repeated exposure. [crystalline silica]

Aspiration hazard: Data not available

Potential health effects:

Inhalation: Brick dust may cause congestion and irritation in nasal and respiratory passages.

Ingestion: Expected to be practically non-toxic. Ingestion of large amounts may cause gastrointestinal irritation and blockage.

Skin: May cause abrasions.

Eyes: May cause mild to severe irritation by abrasion with dust or chips.

Signs and symptoms of exposure: Prolonged inhalation of particulate dust, may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis.

Additional information: RTECS #: None listed

Section 12 **Ecological information**

Toxicity to fish: No data available

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available

Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: Not applicable Shipping name: Not Regulated Hazard class: Not applicable Packing group: Not applicable

2020 ERG Guide # Not applicable

Reportable Quantity: No

Marine pollutant: No

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory lis

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Granite	Not listed	Not listed	Not listed	Not listed	Not listed	

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure ERG: Emergency Response Guidebook.

Form 06/2015

Exceptions: Not applicable

Revision Date: October 1, 2020 Supercedes: February 1, 2019

Identification

Page E1 of E2

Innovating Science® by Aldon Corporation "cutting edge science for the classroom"

221 Rochester Street Avon, NY 14414-9409 (585) 226-6177 CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

Product SANDSTONE

Synonyms Aggregate

Section 2 Hazards identification

This substance or mixture has not been classified as hazardous according to the Globally Harmonized System (GHS) of Classification and Labeling of Chemicals

Signal word: WARNING Pictograms: GHS08

Target organs: Central nervous system, Respiratory system, Eyes, Skin



GHS Classification:

*STOT-RE (Category 2)

GHS Label information: Hazard statement:

*H373: May cause damage to organs (*lungs*) through prolonged or repeated exposure (*inhalation*).

* Respirable dust particles containing silicon dioxide may be generated by crushing. There are no known hazards associated with this material when used as recommended.

Precautionary statement:

P260: Do not breathe dust.

P314: Get medical advice/attention if you feel unwell.

P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / info	rmation on ingredients		
Chemical Name	CAS#	%	EINECS
Silicon dioxide	14808-60-7	77-79%	231-545-4
Calcium oxide	1305-78-8	5-6%	215-138-9
Aluminum oxide	1344-28-1	4-5%	None assigned
Potassium oxide	12136-45-7	1-2%	None assigned
Ferric oxide	1309-37-1	1-2%	None assigned
Ferrous oxide	1345-25-1	1-2%	None assigned
Magnesium oxide	1309-48-4	1-2%	215-171-9
Sodium oxide	1313-59-3	<1%	235-641-7

Section 4 First aid measures

INGESTION: Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: PROLONGED INHALATION OF PARTICULATE DUST MAY BE HARMFUL. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: MAY CAUSE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY CAUSE ABRASIONS. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Product will not burn or support fire. Use any media suitable for extinguishing supporting fire

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool..

Specific Hazards: None known.

Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Do not inhale dusts. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits.	Particles not otherwise classified	TWA: 5 mg/m ³ respirable fraction	None established	None established			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If dusty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical and chemical properties

Appearance: Solid. Multi-colored angular pieces.

Odor: No odor.

Odor threshold: Data not available.

pH: Data not available.

Melting / Freezing point: Data not available

Boiling point: Data not available Flash point: Not flammable

Evaporation rate (= 1): Not applicable Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: Not flammable Vapor pressure (mm Hg): Data not available Vapor density (Air = 1): Data not available

Relative density (Specific gravity): 2.5-2.7 Solubility(ies): Insoluble in water.

Partition coefficient: Not applicable
Auto-ignition temperature: Not applicable
Decomposition temperature: Data not available.

Marine pollutant: No

Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture

Section 10 Stability and reactivity

Chemical stability: Stable

Hazardous polymerization: Will not occur.

Conditions to avoid: Contact with incompatible materials.

Incompatible materials: Strong oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride and oxygen difluoride may cause fire and/or explosion. Silica dissolves in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride.

Hazardous decomposition products: Silica containing respirable dust particles may be generated by handling. When heated, quartz is slowly transformed into tridymite (>860°C/1580°F) and cristobalite (>1470°/2678°F).

Section 11 Toxicological information

Acute toxicity: Data not available

Skin corrosion/irritation: Data not available Serious eye damage/irritation: Data not available Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: Known to be a human carcinogen (respirable). [crystalline silica] IARC classified: Group 1: Carcinogenic to humans. [crystalline silica]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. Ca Prop 65: A WARNING! This product can expose you to a chemical, crystalline silica, which is known to the State of California to cause cancer.

Reproductive toxicity: Data not available STOT-single exposure: Data not available

STOT-repeated exposure: Inhalation - May cause damage to organs through prolonged or repeated exposure. [crystalline silica]

Aspiration hazard: Data not available

Potential health effects:

Inhalation: Brick dust may cause congestion and irritation in nasal and respiratory passages.

Ingestion: Expected to be practically non-toxic. Ingestion of large amounts may cause gastrointestinal irritation and blockage.

Skin: May cause abrasions.

Eyes: May cause mild to severe irritation by abrasion with dust or chips.

Signs and symptoms of exposure: Prolonged inhalation of particulate dust, may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis.

Additional information: RTECS #: None listed

Section 12 Ecological information

Toxicity to fish: No data available

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available

Persistence and degradability: No data available Mobility in soil: No data available

Bioaccumulative potential: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: Not applicable Shipping name: Not Regulated

Hazard class: Not applicable

Exceptions: Not applicable

Packing group: Not applicable

2020 ERG Guide # Not applicable

king group: Not applicable Reportable Quantity: No

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Sandstone	Not listed	Not listed	Not listed	Not listed	Not listed	⚠ WARNING -Cancer - www.P65Warnings.ca.gov.

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

Form 06/2015 Revision Date: October 16, 2020 Supercedes: February 4, 2019