

F v9A moo.laiigital.com

112-762-2260 • FX: 715-762-2719 Non Typical, Inc. • 860 Park Lane • Park Falls, WI 54552



- theil @1 ni-tlin8
- built-in rechargeable lithium battery
- e View, transfer and delete images
- Compatible with CompactFlash and SD cards

(2) this device must accept any interference received, including interference that may cause undesired operation.

(1) this device may not cause harmful interference, and

This device complies with Parl 15 of the FCC Rules. Operation is subject to the following two conditions:

SD/CF "archive" card. high-capacity (we recommend 2.0GB) each camera's CF/SD card to a single, CuddeView, transfer images from each scouting camera and, using Eliminate card swapping! Check

video-in port). ADA seruires MCA (TV requires RCA so you can see your scouting camera CuddeView comes with a TV cable

- VT 900 no səbami wəiV .

USB port and Windows XP/Vista operating system). download images to your computer (cable included; requires CuddeView serves as a PC or laptop card reader, so you can

2. View images on your computer -

Use CuddeView to view your images in the field.

- bleif edf in ages in the field -

digital scouting camera images. to view, transfer and delete your CuddeView is the ONLY device you need

CuddeView 4-in-1 Field Viewer New from Cuddeback ... the

Introduction

Thank you for purchasing a Cuddeback Capture IR digital scouting camera. Capture IR is so easy to use that you may feel you do not need to read this manual. However, we recommend you spend 5 minutes reading this manual to familiarize yourself with the not-so-obvious features of the Capture IR. At the very least, read on how to check your Capture IR.

What You Need


Before you can use your Capture IR, you will need the following items:

- 1. One or more Secure Digital (SD) cards. We recommend sizes up to 2 GB, with 1 GB being the preferred size. The higher the number on the card, the more images that can be saved on the card. DO NOT USE SDHC CARDS.
- 2. Four D Cell batteries (we recommend Rayovac, Duracell or Energizer brand batteries).
- 3. An optional padlock if you want to prevent tampering. The shaft of the padlock must be 1/4 inch or smaller to fit through the Capture IR's padlock opening.



STEP 1 - Familiarize Yourself with Capture IR

Take a moment to familiarize yourself with Capture IR's parts.



STEP 2 - Turning Capture IR On

- 1. Mount the supplied tree bracket to the back of the camera with the supplied screw
- 2. Turn the rotary switch to the OFF position.
- 3. Install 4 new alkaline D cell batteries. Make sure to observe correct polarity.
- 4. A series of numbers will be displayed. These are the Capture IR's hardware and software version numbers.
- 5. Wait until the LCD display goes blank and the green & red LEDs turn off.
- 6. Install SD card. We recommend a 1 GB size card.

STEP 3 - Setting up the Capture IR

Turn the rotary switch to **Time** position, press A to set hour and B to set minutes. Time is AM/PM format.

Turn the rotary switch to **Date** position, press A to set month and B to set day.

Turn the rotary switch to **Year** position, press A to go back and B to go forward.

STEP 4 - Attaching Capture IR to a Tree

Attach Capture IR to a tree with the supplied strap. For optimum detection of "deer size" animals we recommend mounting the Capture IR about 3 feet from the ground. For best image quality, install Capture IR about 10 to 15 feet from the area animals are expected. However, the Capture IR will detect animals at distances from directly in front of the camera to about 50 feet. Note that detection distance varies greatly with air temperature, subject size and movement speed.

It is best to remove any vegetation and obstructions from the Capture IR's field of view as they may interfere with the Capture IR's sensor or camera.

Aim/align the Capture IR to make sure it is pointed where you expect the animals to be. You can use the Capture IR's Test feature, as explained next, to help you determine the detection zone.

STEP 5 - Checking the Capture IR's Detection Zone

Turn the rotary switch to the Test position. Close the cover and tighten the thumb screw. Walk back and forth in front of Capture IR. The red LED will illuminate when the Capture IR's sensor has detected you. Using this method you can accurately position your Capture IR as desired.

STEP 6 - Arming the Capture IR

Turn the rotary switch to one of five Armed delay settings. These settings represent the amount of time the Capture IR will wait before it will take another image. This dwell time prevents multiple images of the same animal.

30 seconds - best setting for game trails

1 minute – use on scrapes

5 minutes - food plots or feed stations

15 minutes - feed stations

30 minutes - feed stations

When first armed, the Capture IR will display the indicated delay for 5 seconds and then begin counting down from 40 to 0. When the counter gets to 0 the Capture IR will arm and be ready to record images. This gives you time to leave the area. Once the Capture IR takes a picture, the LCD will display the delay setting and begin counting down. Once the counter reaches "0" the Capture IR is ready to record the next image.

STEP 7 - Checking Capture IR

Note - When you approach the Capture IR it will probably take a picture of you. This should not be a concern as the image can be deleted later. Open the cover and the LCD display will probably be counting down as the Capture IR will be in the delay or dwell time after taking your photo.

Press the A or B switch to temporarily suspend the Armed mode. The number of images on the SD card will be displayed. Press the A or B switch again to view additional information. Here is the sequence of data that is displayed each time the A or B key is pressed.

- a. Images on SD card. (Note the ARMED, DWELL, & IMAGES icons are displayed.)
- b. Free Space on SD card in MB. (Note that ARMED & DWELL icons are displayed.)
- c. Time
- d. Date
- e. Year
- f. -, dashes indicate the Capture IR is in Test mode and will illuminate the red LED when activity is seen. Capture IR will automatically [auto arm] in about 4 minutes. This allows you to close the cover and leave the area.

Pressing the A or B switch again will auto arm the Capture IR.

STEP 8 - Viewing Images

Once you have the Capture IR in one of these states (a thru ${\bf f}$ - see step 7) remove the SD card.

Do not remove the SD card if the green LED is illuminated.

There are three ways to view images. **First**, you can view the images with an optional viewer or a point-and-shoot camera that is able to read Capture IR images (NOTE: not all SD-based cameras can view Capture IR images, please test any camera before purchasing).

Second, replace the SD card with a fresh SD card and take the original SD card with you to view on your PC or other device.

Third, Cuddeback's CuddeView 4-in-1 viewer will allow you to view the images, copy the images to a CF card, erase the images from the SD card, and then put the original SD card back into Capture IR. CuddeView allows you to use one CF card to record images from multiple cameras. See www.cuddebackdigital.com for more information on CuddeView.

Using Capture IR without SD Card

When Capture IR is used without an SD card, images are stored in Capture IR's internal image memory. Capture IR features an internal memory of about 30 MB. This may allow storage of up to 100 images. Images can be transferred from internal memory to an SD card.

If you use the Capture IR without an SD card, follow these steps to transfer the images from the internal memory to an SD card.

- 1. Turn the rotary switch to OFF, and wait until the LCD goes blank.
- 2. Wait until the green LED turns off and then install an SD card.
- Turn the rotary switch to any other setting, such as Set Time. The green LED will turn on.
- 4. When the green LED turns off (NOTE: You may need to wait up to 3 minutes) the images have been copied from the internal memory to the SD card.

DO NOT REMOVE OF INSTALL the SD CARD WHEN THE GREEN LED IS ON.

Battery Life & Low Battery Warning

The life of the batteries in your Capture IR will vary depending upon battery quality, ambient temperature, and the number of images taken. Our testing shows that Capture IR will take over 2,000 images on a single set of batteries (at room temperature). You may get more or less than 2,000 depending on your circumstances. We strongly recommend you use Rayovac, Duracell, or Energizer brand batteries.

Replace Capture IR batteries when 1) "B LOW" appears on the LCD screen (which stands for batteries low) or 2) Capture does not appear to operate correctly (in some cases the batteries may be too low to even turn on the B LOW icon).

Use your Windows PC to manage Cuddeback images with Trophy Room Image Management Software

Trophy Room Image Management Software will revolutionize scouting camera image management and how you use your images to make you a better hunter.

Trophy Room is a full-featured PC program that:

- Automatically copies images from your SD or CF card to your PC. It even erases the card when finished.
- Organizes your images by the year and date they were copied to your PC.
- Allows you to rename each folder to make it easy to find your images.
- Displays sun and moon data for each image, including moon phase, moon rise & set, sunrise & set, and even moon and sun position in the sky at the time the image was taken.
- Categorizes images as buck, doe, fawn, bear, etc. There are 28 categories
 to select from. For whitetail deer, you can enter point count and give the deer
 a name to allow easy monitoring of trophy animals.
- Automatically calculates the buck/doe/fawn ratios based upon your images.
- With the CuddeCharts feature you can analyze your images to determine peak movement patterns based upon sun and moon phase and position.
- With the Crystal Ball feature, you can use the data you collected and analyzed with CuddeCharts to predict future activity. Think of this as the traditional moon tables, only much better and tailored to you.

Best of all, **Trophy Room** is free and works with all Cuddeback cameras. You can get it at <u>www.cuddebackdigital.com</u>.